

质量合格证

ExxonMobil

Lubricants & Specialties

ExxonMobil Trading Co. (Shanghai) Ltd.
1099 Century Avenue, Pudong, Shanghai
Date: 19/07/2025

Product Name: MOBIL DTE FM 220 FOOD

Packaging: 18.9 L (Drum)

Batch Number	70486715	Packaging Type	Drum
Internal Code		Production Date	19/07/2025
Shipping Number		Destination	
Product Code		Reference	

Item	Test Method	Result
Kinematic Viscosity @40°C (cSt)	ASTM D445	45.5
Kinematic Viscosity @100°C (cSt)	ASTM D445	6.5
Pour Point (°C)	ASTM D595	-28
Appearance	Visual	Colorless / Transparent
Oxidation Stability 72h @54°C	FTM 791.3459	Pass
Flash Point (°C)	ASTM D92	275
Foaming Characteristics	ASTM D892	0
Viscosity Index	ASTM D2270	141
Odor	AM-S 1695	Pass
Water Content	M449	None
Density @ 60°F (g/cc)	ASTM D4052	0.855

This product complies with ExxonMobil specifications for this lubricant and meets ISO9001 certification requirements. The above results are based on the most recent quality control tests performed on this batch.

Hans Zheng
Laboratory Supervisor